

FLEXIBLE SLEEVE MANICOTTO FLESSIBILE SERIES/SERIE FM




Dimensions \ Ingombri

Mod	DN	D (mm)	L (mm)	Min. radius of curvature	Max pressure	Max. negative pressure	Weight Peso (g)
				Raggio di curvatura (mm)	Pressione max (bar)	Depressione max (mbar)	
FM1	15	22	200	15	2,8	650	60
FM2	20	30	200	15	2,8	650	65
FM3	25	32	200	16	2,6	650	90
FM4	32	45	200	21	2,6	560	135
FM4C	32	45	110	21	2,6	560	85
FM5	40	51	250	24	2,6	520	180
FM5C	40	51	130	24	2,6	520	100
FM6	50	64	250	31	2,4	480	200
FM6C	50	64	135	31	2,4	480	120
FM8	80	90	330	44	2,0	400	250
FM9	100	114	330	57	1,6	290	370
FM10	125	140	330	70	1,3	190	400

INTAKE PROTECTION PROTEZIONE IN ASPIRAZIONE SERIES/SERIE IP

Filter for valves **VRL**
Filtro per valvole



Dimensions \ Ingombri

Mod	DN	ØA (mm)	G (mm)	H (mm)	M (mm)	Degree of filtration	Weight Peso (Kg)
						Grado di filtrazione (mm)	
IP4	32	50	G1 ¹ / ₄	75	10	1.200 µm	38
IP5	40	56	G1 ¹ / ₂	83	11	1.200 µm	47
IP6	50	69	G2"	98	13	1.200 µm	70
IP8	80	102	G3"	138	15	2.000 µm	194
IP8N	80	102	3"NPT	138	15	2.000 µm	194
IP9	100	129	G4"	153	16	2.000 µm	300
IP9N	100	129	4"NPT	153	16	2.000 µm	300