

	Δp [mbar]	2000 rpm			2250 rpm			2500 rpm			2750 rpm			2900 rpm			3250 rpm			3500 rpm		
		Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]
DRUCKBETRIEB	225	-	-	-	-	-	-	-	-	-	-	-	-	169	3.72	4.00	-	-	-	-	-	-
	200	-	-	-	-	-	-	-	-	-	166	3.18	4.00	198	3.39	4.00	-	-	-	-	-	-
	175	-	-	-	-	-	-	142	2.55	4.00	195	2.86	4.00	224	3.05	4.00	-	-	-	-	-	-
	150	-	-	-	120	1.98	4.00	174	2.25	4.00	221	2.54	4.00	247	2.72	4.00	-	-	-	-	-	-
	125	101	1.49	4.00	156	1.71	4.00	203	1.96	4.00	245	2.22	4.00	268	2.38	4.00	-	-	-	-	-	-
	100	140	1.24	4.00	186	1.44	4.00	227	1.66	4.00	265	1.90	4.00	286	2.05	4.00	-	-	-	-	-	-
	75	173	1.00	4.00	212	1.17	4.00	248	1.36	4.00	282	1.58	4.00	302	1.71	4.00	-	-	-	-	-	-
	50	199	0.75	4.00	233	0.90	4.00	265	1.07	4.00	297	1.26	4.00	315	1.38	4.00	-	-	-	-	-	-
	25	218	0.51	4.00	248	0.63	4.00	278	0.77	4.00	308	0.94	4.00	326	1.04	4.00	-	-	-	-	-	-
	0	230	0.27	4.00	259	0.36	4.00	288	0.48	4.00	317	0.62	4.00	334	0.71	4.00	-	-	-	-	-	-
VAKUUMBETRIEB	25	221	0.56	4.00	251	0.68	4.00	280	0.81	4.00	309	0.95	4.00	326	1.05	4.00	-	-	-	-	-	-
	50	205	0.80	4.00	236	0.94	4.00	267	1.10	4.00	298	1.27	4.00	316	1.38	4.00	-	-	-	-	-	-
	75	179	1.04	4.00	214	1.21	4.00	248	1.40	4.00	281	1.59	4.00	300	1.71	4.00	-	-	-	-	-	-
	100	143	1.28	4.00	184	1.48	4.00	222	1.69	4.00	258	1.91	4.00	279	2.05	4.00	-	-	-	-	-	-
	125	-	-	-	146	1.74	4.00	190	1.98	4.00	230	2.23	4.00	252	2.38	4.00	-	-	-	-	-	-
	150	-	-	-	-	-	-	150	2.27	4.00	195	2.55	4.00	221	2.72	4.00	-	-	-	-	-	-
	175	-	-	-	-	-	-	-	-	-	155	2.87	4.00	183	3.05	4.00	-	-	-	-	-	-
	200	-	-	-	-	-	-	-	-	-	-	-	-	140	3.39	4.00	-	-	-	-	-	-

Toleranz auf die angegebenen Werte $\pm 10\%$.

Änderungen der Daten ohne vorherige Ankündigung vorbehalten.

Kennlinien bezogen auf Luft bei einer Temperatur von 20 °C und atmosphärischem Druck von 1013 mbar (abs).