

	Δp [mbar]	2000 rpm			2250 rpm			2500 rpm			2750 rpm			2900 rpm			3250 rpm			3500 rpm		
		Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]
DRUCKBETRIEB	550	-	-	-	-	-	-	-	-	-	-	-	-	157	6.60	7.50	-	-	-	-	-	-
	500	-	-	-	-	-	-	-	-	-	149	5.73	7.50	172	6.11	7.50	226	7.05	7.50	-	-	-
	450	-	-	-	-	-	-	-	-	-	165	5.27	7.50	188	5.63	7.50	241	6.51	7.50	279	7.19	7.50
	400	-	-	-	-	-	-	143	4.27	7.50	181	4.80	5.50	204	5.14	5.50	257	5.98	7.50	295	6.62	7.50
	350	-	-	-	122	3.38	7.50	160	3.84	5.50	198	4.34	5.50	221	4.65	5.50	274	5.44	5.50	311	6.05	7.50
	300	102	2.59	7.50	140	2.99	5.50	178	3.42	5.50	216	3.87	5.50	239	4.17	5.50	291	4.90	5.50	328	5.48	7.50
	250	121	2.24	5.50	160	2.60	5.50	198	2.99	5.50	235	3.41	4.00	258	3.68	4.00	309	4.37	5.50	345	4.91	5.50
	200	143	1.89	5.50	181	2.21	4.00	219	2.56	4.00	255	2.94	4.00	277	3.19	4.00	328	3.83	4.00	363	4.34	5.50
	150	167	1.53	4.00	204	1.81	4.00	240	2.13	4.00	276	2.48	4.00	298	2.71	4.00	347	3.30	4.00	381	3.77	4.00
	100	193	1.18	4.00	228	1.42	4.00	264	1.70	4.00	298	2.01	4.00	319	2.22	4.00	366	2.76	4.00	400	3.20	4.00
	50	221	0.82	4.00	254	1.03	4.00	288	1.27	4.00	321	1.55	4.00	341	1.73	4.00	386	2.22	4.00	419	2.63	4.00
VAKUUMBETRIEB	0	251	0.47	4.00	282	0.64	4.00	313	0.84	4.00	344	1.08	4.00	363	1.25	4.00	407	1.69	4.00	438	2.05	4.00
	50	224	0.88	4.00	256	1.07	4.00	288	1.29	4.00	320	1.52	4.00	339	1.67	4.00	384	2.06	4.00	416	2.36	4.00
	100	195	1.21	4.00	228	1.44	4.00	262	1.70	4.00	295	1.97	4.00	314	2.14	4.00	360	2.58	4.00	392	2.92	4.00
	150	163	1.55	4.00	199	1.82	4.00	233	2.11	4.00	267	2.42	4.00	288	2.61	4.00	334	3.10	4.00	367	3.47	4.00
	200	129	1.88	5.50	167	2.19	4.00	203	2.52	4.00	238	2.86	4.00	259	3.08	4.00	308	3.62	4.00	342	4.03	5.50
	250	-	-	-	132	2.56	5.50	171	2.93	4.00	208	3.31	4.00	230	3.55	4.00	280	4.14	5.50	315	4.58	5.50
	300	-	-	-	-	-	-	137	3.34	5.50	176	3.76	5.50	199	4.02	5.50	251	4.66	5.50	287	5.14	5.50
	350	-	-	-	-	-	-	-	-	-	142	4.20	5.50	166	4.49	5.50	220	5.18	5.50	258	5.69	7.50
	400	-	-	-	-	-	-	-	-	-	-	-	-	132	4.96	5.50	189	5.70	7.50	227	6.25	7.50

Toleranz auf die angegebenen Werte $\pm 10\%$.

Änderungen der Daten ohne vorherige Ankündigung vorbehalten.

Kennlinien bezogen auf Luft bei einer Temperatur von 20 °C und atmosphärischem Druck von 1013 mbar (abs).