

	Δp [mbar]	2000 rpm			2250 rpm			2500 rpm			2750 rpm			2900 rpm			3250 rpm			3500 rpm			3750 rpm*			4000 rpm*		
		Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]	Q [m³/h]	P [kW]	P _n [kW]
DRUCKBETRIEB	550	-	-	-	-	-	-	-	-	-	-	-	-	550	16.05	18.50	-	-	-	-	-	-	-	-	-	-	-	-
	500	-	-	-	-	-	-	-	-	-	522	13.94	18.50	573	14.93	18.50	693	17.37	18.50	-	-	-	-	-	-	-	-	-
	450	-	-	-	-	-	-	459	11.40	18.50	546	12.87	18.50	597	13.80	15.00	715	16.14	18.50	-	-	-	-	-	-	-	-	-
	400	-	-	-	-	-	-	485	10.41	15.00	571	11.80	15.00	622	12.68	15.00	738	14.90	18.50	820	16.63	18.50	-	-	-	-	-	-
	350	-	-	-	426	8.22	15.00	512	9.42	15.00	596	10.73	15.00	647	11.56	15.00	762	13.66	15.00	843	15.31	18.50	923	17.09	18.50	-	-	-
	300	368	6.29	15.00	455	7.32	15.00	539	8.43	15.00	623	9.65	15.00	672	10.44	11.00	785	12.43	15.00	865	14.00	15.00	944	15.70	18.50	1023	17.53	18.50
	250	399	5.47	15.00	484	6.41	15.00	568	7.44	11.00	649	8.58	11.00	698	9.31	11.00	810	11.19	15.00	888	12.68	15.00	966	14.30	18.50	1044	16.06	18.50
	200	432	4.66	11.00	515	5.51	11.00	597	6.46	11.00	677	7.51	11.00	724	8.19	11.00	834	9.95	11.00	912	11.36	15.00	989	12.90	15.00	1065	14.58	18.50
	150	466	3.84	11.00	547	4.60	11.00	626	5.47	11.00	705	6.43	11.00	751	7.07	11.00	859	8.72	11.00	936	10.05	11.00	1011	11.51	15.00	1087	13.11	15.00
	100	501	3.02	11.00	580	3.70	11.00	657	4.48	11.00	733	5.36	11.00	779	5.95	11.00	885	7.48	11.00	960	8.73	11.00	1034	10.11	11.00	1108	11.63	15.00
	50	538	2.20	11.00	614	2.79	11.00	688	3.49	11.00	763	4.29	11.00	807	4.83	11.00	910	6.24	11.00	984	7.41	11.00	1057	8.71	11.00	1130	10.16	11.00
VAKUUMBETRIEB	0	576	1.38	11.00	648	1.89	11.00	720	2.50	11.00	792	3.22	11.00	836	3.70	11.00	937	5.01	11.00	1009	6.09	11.00	1081	7.32	11.00	1153	8.68	11.00
	50	543	2.38	11.00	617	2.95	11.00	690	3.58	11.00	763	4.27	11.00	806	4.72	11.00	908	5.87	11.00	980	6.77	11.00	1053	7.75	11.00	1125	8.79	11.00
	100	504	3.08	11.00	580	3.72	11.00	655	4.43	11.00	730	5.20	11.00	774	5.70	11.00	878	6.95	11.00	951	7.92	11.00	1024	8.97	11.00	1098	10.09	11.00
	150	458	3.77	11.00	537	4.49	11.00	615	5.28	11.00	692	6.12	11.00	738	6.67	11.00	844	8.02	11.00	919	9.07	11.00	993	10.19	11.00	1067	11.38	15.00
	200	404	4.47	11.00	488	5.26	11.00	570	6.13	11.00	650	7.05	11.00	698	7.64	11.00	806	9.10	11.00	883	10.22	11.00	959	11.42	15.00	1035	12.68	15.00
	250	-	-	-	433	6.04	11.00	520	6.97	11.00	604	7.98	11.00	653	8.61	11.00	765	10.17	11.00	844	11.37	15.00	922	12.64	15.00	999	13.98	15.00
	300	-	-	-	-	-	-	465	7.82	15.00	553	8.90	11.00	604	9.58	11.00	721	11.25	15.00	802	12.52	15.00	882	13.86	15.00	961	15.27	18.50
	350	-	-	-	-	-	-	-	-	-	497	9.83	15.00	551	10.55	11.00	673	12.32	15.00	757	13.67	15.00	840	15.09	18.50	921	16.57	18.50
	400	-	-	-	-	-	-	-	-	-	437	10.75	15.00	494	11.52	15.00	622	13.40	15.00	709	14.82	18.50	794	16.31	18.50	-	-	-
	450	-	-	-	-	-	-	-	-	-	-	-	-	433	12.49	15.00	567	14.47	18.50	658	15.97	18.50	746	17.53	18.50	-	-	-

Toleranz auf die angegebenen Werte $\pm 10\%$.

Änderungen der Daten ohne vorherige Ankündigung vorbehalten.

Kennlinien bezogen auf Luft bei einer Temperatur von 20 °C und atmosphärischem Druck von 1013 mbar (abs).

* Nur für GOR / GVR Ausführung